

Rev No	Change	ECN
31.10.13	HEAD DIA CHANGED TO 6-8mm INSTEAD OF (7MAX)	--

2	31.10.14	DIVIDING LENGTH CHANGED FOR THIS PART SUPPLIED	--
3	23.10.16	WIRE LENGTH ADDED & RESING CHANGED	--
4	13.12.18	WIRE LENGTH ADDED BASE ON CUSTOMER DEMAND	--

Age	ECN
5-8mm INSTEAD OF(7MAX)	--
CHANGED FOR THIS PART SUPPLIED	--
RESINING CHANGED	--
BASE ON CUSTOMER DEMAND	--

CHARACTERISTICS

RESISTANCE VS TEMPERATURE

- | TEMP (°C) | RESISTANCE IN OHM |
|-----------|-------------------|
| -40.0 | 333563.0 |
| -35.0 | 241072.0 |
| -30.0 | 176061.0 |
| -25.0 | 129925.0 |
| -20.0 | 96807.0 |
| -15.0 | 72899.0 |
| -10.0 | 55253.0 |
| -5.0 | 42292.0 |
| 0.0 | 32640.0 |
| 5.0 | 25390.0 |
| 10.0 | 19901.0 |
| 15.0 | 15713.0 |
| 20.0 | 12490.0 |
| 25.0 | 10000.0 |
| 30.0 | 8057.0 |
| 35.0 | 6532.0 |
| 40.0 | 5327.0 |
| 45.0 | 4364.0 |
| 50.0 | 3598.0 |
| 55.0 | 2980.0 |
| 60.0 | 2464.0 |
| 65.0 | 2000.0 |
| 70.0 | 1750.0 |
| 75.0 | 1476.0 |
| 80.0 | 1253.0 |
| 85.0 | 1070.0 |

03	RMW-1001-PA	22 AWG BALCK PVC INSULATED TWIN CABLE RATED 105°C
02	RMR-1016-X RMR-1003-X	RESIN
01	TNT-1001-L250	NTC THERMISTOR
SL NO.	TST PART NO.	MATERIAL DESCRIPTION

MATERIAL PART LIST

03	RMW-1001-PA	22 AWG BALCK PVC INSULATED TWIN CABLE RATED 105°C
02	RMR-1016-X RMR-1003-X	RESIN
01	TNT-1001-L250	NTC THERMISTOR
SL NO.	TST PART NO.	MATERIAL DESCRIPTION

13.12.18	5		..	
----------	---	---	----	---

PROJECTION		SCALE		SHEET	
		NTS		1 OF 1	
TOLERANCES UNLESS SPECIFIED					
OVER	3	6	30	120	315 1000 2000
UP TO	3	6	30	120	315 1000 2000
±	0.05	0.1	0.15	0.2	0.3 0.4 1.0 2.0
				ANGLE (°)	
				RIGHT	
				OTHER	
				1.5	

The copyright of this Specification/Drawing is the property of THOMSONS TECHNOLOGIES PVT. LTD and it is loaned on the condition that it is not to be copied, reprinted or stored in any manner without the consent of THOMSONS TECHNOLOGIES PVT. LTD. The user shall indemnify and hold harmless THOMSONS TECHNOLOGIES PVT. LTD from and against all claims, damages, costs and expenses, including legal fees, which may be incurred by THOMSONS TECHNOLOGIES PVT. LTD in connection with the use of this Specification/Drawing.

13.12.18	5	1	..	1
23.10.16	4	..	..	SJ
31.10.14	3	..	..	..
31.10.13	2	..	..	..
11.02.11	1	NEP	..	SJ
DATE	ISS	DRN	CHD	APD